

Read from Remote Database Element

Reads sequences and annotations if any from a remote database.

Parameters in GUI

Parameter	Description	Default value
Resource IDs (required)	Semicolon-separated list of resource IDs in the database.	
Database (required)	Name of the database to read from.	NCBI Genbank (DNA sequence)
Save file to directory	Directory to store a file loaded from the database.	default
Read resource ID(s) from source	The source to read resource IDs from: the list or a local file.	List of TDs

Parameters in Workflow File

Type: fetch-sequence

Parameter	Parameter in the GUI	Type
resource-id	Resource IDs	<i>string</i>
database	Database	<i>string</i> Available values are: • ncbi-dna (NCBI GenBank (DNA sequence)) • ncbi-protein (NCBI protein sequence database) • pdb (PDB) • swiss-plot (SWISS-PROT) • uniprot-swiss-prot (UniProtKB/Swiss-Prot) • uniprot-trembl (UniProtKB/TrEMBL)
save-dir	Save file to directory	<i>string</i>
ids-source	Read resource ID(s) from source	<i>string</i>

Input/Output Ports

The element has 1 *output port*:

Name in GUI: *Sequence*

Name in Workflow File: out-sequence

Slots:

Slot In GUI	Slot in Workflow File	Type
Sequence	sequence	<i>sequence</i>
Set of annotations	annotations	<i>annotation-table</i>