## **Map Reads with Bowtie Element**

Performs alignment of short reads with Bowtie.

Element type: align-reads-with-bowtie

## **Parameters**

Parameter	Description	Default value	Parameter in Workflow File	Туре
Output directory	Directory to save Bowtie output files.		output-dir	string
Reference genome	Path to an indexed reference genome.		reference	string
Output file name	Base name of the output file. 'out.sam' by default.	out.sam	outname	string
Library	Is this library mate-paired?	single-end	library	string
Mode	When the -n option is specified (which is the default), bowtie determines which alignments are valid according to the following policy, which is similar to Maq's default policy. In -v mode, alignments may have no more than V mismatches, where V may be a number from 0 through 3 set using the -v option. Quality values are ignored. The -v option is mutually exclusive with the -n option.	-n mode	mismatches_ type	string
Mismatches number	Mismatches number.	2	mismatches_ number	numerio
Mismatches number	Maximum permitted total of quality values at all mismatched read positions throughout the entire alignment, not just in the seed. The default is 70. Like Maq, bowtie rounds quality values to the nearest 10 and saturates at 30; rounding can be disabled withnomaground.	70	maqerr	numerio
Seed length	The seed length; i.e., the number of bases on the high-quality end of the read to which the -n ceiling applies. The lowest permitted setting is 5 and the default is 28. bowtie is faster for larger values of -l.	28	seedLen	numerio
Maximum of backtracks	The maximum insert size for valid paired-end alignments. E.g. if -X 100 is specified and a paired-end alignment consists of two 20-bp alignments in the proper orientation with a 60-bp gap between them, that alignment is considered valid (as long as -I is also satisfied). A 61-bp gap would not be valid in that case. If trimming options -3 or -5 are also used, the -X constraint is applied with respect to the untrimmed mates, not the trimmed mates. Default: 250.	800	maxbts	numerio
Best hits	The number of megabytes of memory a given thread is given to store path descriptors inbest mode. Best-first search must keep track of many paths at once to ensure it is always extending the path with the lowest cumulative cost. Bowtie tries to minimize the memory impact of the descriptors, but they can still grow very large in some cases. If you receive an error message saying that chunk memory has been exhausted inbest mode, try adjusting this parameter up to dedicate more memory to the descriptors. Default: 64.	64	chunkmbs	numerio
Seed	Use as the seed for pseudo-random number generator.	0	seed	numerio
Colorspace	When -C is specified, read sequences are treated as colors. Colors may be encoded either as numbers (0=blue, 1=green, 2=orange, 3=red) or as characters A/C/G/T (A=blue, C=green, G=orange, T=red).	False	colorspace	boolear
No Maq rounding	Maq accepts quality values in the Phred quality scale, but internally rounds values to the nearest 10, with a maximum of 30. By default, bowtie also rounds this waynomaground prevents this rounding in bowtie.	False	nomaqround	boolear
No forward orientation	Ifnofw is specified, bowtie will not attempt to align against the forward reference strand.	False	nofw	boolear
No reverse- complement orientation	Ifnorc is specified, bowtie will not attempt to align against the reverse-complement reference strand.	False	norc	boolear
Try as hard	Try as hard as possible to find valid alignments when they exist, including paired-end alignments. This is equivalent to specifying very high values for themaxbts andpairtries options. This mode is generally much slower than the default settings, but can be useful for certain problems. This mode is slower when (a) the reference is very repetitive, (b) the reads are low quality, or (c) not many reads have valid alignments.	False	tryhard	boolear
Best alignments	Make Bowtie guarantee that reported singleton alignments are best in terms of stratum (i.e. number of mismatches, or mismatches in the seed in the case of -n mode) and in terms of the quality values at the mismatched position(s). bowtie is somewhat slower whenbest is specified.	False	best	boolear
All alignment	Report all valid alignments per read or pair.	False	all	boolean

## Input/Output Ports The element has 1 input port.

Name in GUI: Bowtie data

Name in Workflow File: in-data

Slots:

Slot In GUI	Slot in Workflow File	Туре
URL of a file with mate reads	readsurl	string
URL of a file with reads	readspairedurl	string

And 1 output port:

Name in GUI: Bowtie output data

Name in Workflow File: out-data

Slots:

Slot In GUI	Slot in Workflow File	Туре
Assembly URL	assembly-out	string